


Catalog Number: Project Name: Note: Date: Type:

DESCRIPTION

360° 5CCT COB Round Gimbal Recessed Downlight With Integral Driver In Connection Box.
 Directional lighted, tilted 30° , Rotation 360° , 38° beam and a precision lens.
 Provides uniform brightness without scattering or glare.
 Perfect choice for architectural styles such as living rooms, hallways, stairs and hallways .



BASED ON SAMPLE SETTING. ACTUAL LUMENS MAY VARY.

MODEL#	SIZE	WATTAGE	5CCT	LUMENS
2EJCT05WRWH	2inch	5W	2700K	396Lm
			3000K	401Lm
			3500K	415Lm
			4000K	426Lm
			5000K	408Lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
3EJCT08WRWH	3inch	8W	2700K	573Lm
			3000K	608Lm
			3500K	661Lm
			4000K	707Lm
			5000K	654Lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
4EJCT12WRWH	4inch	12W	2700K	861Lm
			3000K	901Lm
			3500K	931Lm
			4000K	992Lm
			5000K	978Lm

FEATURES

- Aluminum die-cast body with adjustable gimbal
 - Spring loaded retention arms allow for easy installation into ceilings with no need for a recessed hole
 - TIR optic provides smooth, uniform light with a 38° beam angle
- Simple snap-in installation is fast and easy
 Tilting gimbal light source for directional lighting

INSTALLATION

No existing recessed housing or junction box required.
 Suitable for most new constructions.
 Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.
 Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed. Energy Star.Title24.


TECHNICAL SPECIFICATION

VOLTAGE	120V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
CRI	90
BEAM ANGLE	38°
MATERIAL	AL+lens
LIFESPAN	≥50,000hours
OPERATING TEMP	(-4°F~ 113°F) -20~45°C
DIMMING	Triac Dimming
RATING	Suitable for Wet Locations
WARRANTY	5 year limited









Catalog Number : Project Name : Note : Date : Type :

38° Beam Angle	30° Tilt Range	360° Rotation	Selectable CCT 2700K,3000K,3500K,4000K,5000K
----------------	----------------	---------------	---



SIZE & DIMENSION & HOLE CUTOUT

Size	Dimension	Hole Cutout
2inch	 <p>2.26" (65±0.5mm) 3.6" (91.5±0.5mm) 4.53" (115±0.5mm) 1.59" (40.5±0.5mm) 2.06" (52±0.5mm)</p>	 <p>Φ2 1/8" (54mm)</p>
3inch	 <p>Φ3.35" (85±0.5mm) 4.92" (125±0.5mm) 1.91" (48.5±0.5mm) 1.81" (46±0.5mm) 1.30" (33±0.5mm)</p>	 <p>Φ2 3/4" (70mm)</p>
4inch	 <p>Φ4.92" (125±0.5mm) 4.72" (120mm) 2.76" (70mm) 2.24" (57±0.5mm) 1.38" (34±0.5mm)</p>	 <p>Φ4 1/4" (108mm)</p>

RECOMMENDED DIMMER


LUTRON				LEVITON	
TG-600PR-WH	TGCL-153PH-LA	SCL-153PH-WH	MSCL-OP153M	6672	
S-600PR-WH	SLV-600P-AL	GT-600P	MACL-153M//MA-R	6674	RNL06
CTCL-153PDH-WH	DV-600PR-WH	DVCL-153P	PD-6WCL	DSL06	IPL06



J-Box driver



Connector



Hole cutout card