

## **Commercial Grade E Series**

Led Split Deep Regress Commercial Downlight

Catalog Number: Project Name: Note: Date: Type:



- LED split deep regress commercial downlight series are available in 3 different light engine. Each light engine could fitting 6", 8", 10" round trims.
- The innovative separable design of junction box and trim makes it more flexible. One engine allows for seamless integration of multiple trim sizes with easy and tool-free installation.
- Easy-fit installation comes from the adjustable butterfly clips. It is designed for recessed application
- It is suitable for commercial and public places and elegantly decorates the ambience, such as shopping mall, hospital, airport, hotel lobby etc.

#### **FEATURES**

- Spun aluminum reflector integrate with haze finish and white trim ring with shadow free.
- Durable tension clips, allow for fast and easy flush installation.
- 0-10V dimmable.
- Available in 3 wattages and 5 CCT tunable.

#### **TECHNICAL SPECIFICATION**

120-277V	VOLTAGE
50/60Hz	POWER FREQUENCY
>0.9	POWER FACTOR
2700K   3000K   3500K  4000K   5000K	5CCT
90	CRI
90°   70°   50°	BEAM ANGLE
AL+PC	MATERIAL
Balck+Silver	COLOR
≥50,000hours	LIFESPAN
(-4°F~ 113°F) -20~45°C	OPERATING TEMP
0-10V dimmable	DIMMABLE
Suitable for Wet Locations	RATING
5 year limited	WARRANTY









#### INSTALLATION

Easy assembly, tool-free installation.

#### **ELECTRICAL**

This fixture is built with the highest quality drivers, ensuring energy efficiency.

#### **ENERGY SAVINGS**

80% more energy savings than halogen lamps.

#### **LISTING**

ETL Listed.







MUDEL	Ţ	TRIM	1	WALIAGE	- 1	LUMEN
SPCM65DR05	1	DT-6R		45W-55W-65W		3850lm/4700lm/5550lm
	1	DT-8R	1			4050lm/4950lm/5850lm
		DT-10R	İ			4300lm/5250lm/6150lm



# **Commercial Grade E Series**

Led Split Deep Regress Commercial Downlight

Catalog Number: Project Name: Note: Date: Type:



Selectable CCT & Selectable Wattage

The innovative separable design of junction box and trim makes it more flexible.

Easy-fit installation comes from the adjustable butterfly clips.







	6" Light Engine	ı	8" Light Engine	)	10" Light I	Engine	Hole Cutout
6" Round Trim	8 077005em) 4 697119.2mm) (1970)	9.02'(229mm)	8 077005mm) 4.6 697(19.20mm)	9.02 (229mm) 9.17 (86 6mm)	8 0.7.7055mm) 4 469(119.2.mm) 0)	9.02'(229mm)	Hole Size
_	3357(857	1.58 (40.22	\$.62'(1427m)	1.58"(40.22	77(177.7mm) 3.74(85mm)	1.58°(40.22	Φ4 21/64"(110mm)
8" Round Trim	10.02/05/smm) 4.69/T19/2mm)	9.02*(229mm) (w	10 GG/T6Semm) 4.69/T192.mm)	9.02.(555 Smm) (n	10.007(256mm) 4.697719.7mm)	9 02*(229mm) (uu	Hole Size
	5.42*(137.7mm) 3.35*(95mm)	1.58°(40.22mm	\$.01'(1527mm) 3.14'(94mm)	1.58°(40.22nrr	7.39°(187.7mm)	1.55′(40.22n	Ф6 19/64" (160mm)
10" Round Trim		9.02'(229mm)	11.40(1900mm) 1.40(11.10 mm) 1.40(11.10 mm)	m) 3.41/(86.5mm)	11.427260mm) 4.6921132mm)	3.02,(55abum) 3.03,(565amm)	Hole Size
	5.42(137.7mm)	1.58 <sup>(40.22mm)</sup>	6.017(182.7mm) 3.147(96mm)	1.58'(4022m	7.39′(187.7mm) 3.74′(95mm)	1.587(40.22mm	( <u>Г</u> Ф8 31/32" (228mm)

### **RECOMMENDED DIMMER**

	LEGRAND			
RMJS-8T-DV-B	Diva DVSTV	MS-Z101-WH	DVSTV-WH	RH4FBL3PW